



La lampada “**LAMP CP22**” risolve il problema dell’illuminazione nei quadri elettrici e grazie alla presa integrata permette l’utilizzo di piccole apparecchiature elettriche durante la manutenzione.

“**LAMP CP22**” lamp solves problems of lighting in cabinets and by integrated socket allows the use of electrical devices during maintenance.

## CARATTERISTICHE TECNICHE

- Modello: **LAMP CP22** 220 V 50 Hz con presa integrata  
**LAMP SP22** 220 V 50 Hz senza presa
- Lampada: fluorescente con accenditore integrato
- Luminosità: 900 Lm
- Potenza: 11 W
- Durata: 5000 h
- Interruttore: on/off
- Presa: 6 A
- Connessione: morsettiera a 3 poli 2,5 mm<sup>2</sup>
- Montaggio: su guida DIN 35 mm. o su parete con staffa o magnete opzionali
- Contenitore: alluminio anodizzato e plastica autoestinguente
- Dimensioni: 268x92x43 (LxHxP)
- Peso: 760 g.
- Grado di protezione: Ip20
- Marchi: CE

## TECHNICAL FEATURES

- Model: **LAMP CP22** 220 V 50 Hz with socket  
**LAMP SP22** 220 V 50 Hz without socket
- Lamp: fluorescent lamp with integrated starter
- Luminosity: 900 Lm
- Power: 11 W
- Service life: 5000 h
- Switch: on/off
- Socket: 6 A
- Connections: 3 pole terminals 2,5 mm<sup>2</sup>
- Mounting: on DIN 35 mm. or on wall with optional magnet or bracket
- Casing: bright anodised aluminium and grey self-extinguish plastic
- Dimensions: 268x92x43 (WxHxD)
- Weight: 760 g.
- Protection degree : Ip20
- Approval: CE